



PHASICS
The phase control company

SID4 SWIR

COST-EFFECTIVE SHORT WAVE IR WAVEFRONT SENSOR

The SID4 SWIR wavefront sensor integrates PHASICS patented technology with an InGaAs detector. Thanks to its high spatial resolution (80 x 64 phase pixels) and high sensitivity, it offers accurate wavefront measurement from 900 nm to 1.7 μ m. SID4 SWIR is an innovative solution for testing SWIR lens used in optical communications, inspection instruments or night vision in military and surveillance devices.

APPLICATIONS: [Laser industry](#) | [FSOC](#) | [Automotive](#) | [Aerospace](#) | [Optical components](#)

SPECIFICATIONS

** with SID4 software*

Wavelength range	0.9 - 1.7 μ m
Aperture dimensions	9.60 x 7.68 mm ²
Phase spatial resolution	120 μ m
Phase & Intensity sampling	80 x 64
Resolution (Phase)	< 2 nm RMS
Accuracy (Absolute)	15 nm RMS
Frame rate	30 fps
Real-time processing frequency	>7 fps (full resolution)*
Interface	Giga Ethernet
Dimensions	100 x 55 x 63 mm ³
Weight	~ 500g

記載内容および画像の転載、複製、加工などは禁止です。また、記載内容は予告なく変更することがあります。ご了承ください。

_2210