



# Gooch & Housego



## AO Frequency Shifter / Modulator

I-FS110-2C2B8-3-GH2

Former model number: M110-2B/F-GH2

A general purpose, polarisation insensitive, 40MHz frequency shifter or modulator, suitable for use over the range 633 – 680nm.

In addition to the specifications indicated, we also offer alternative wavelengths, frequency shift, active aperture and custom housing configurations.

Our team of engineers and scientists are ready to discuss your requirements and help you find the optimum solution for your individual application.

### Key Features:

- 480 – 800nm
- Polarisation insensitive
- 2mm active aperture
- 110MHz
- Custom configurations available

## General Specifications

Interaction material:	Tellurium Dioxide (TeO <sub>2</sub> )
Acoustic mode:	Compressional
Wavelength:	480 - 800nm
AR coating reflectivity:	≤ 0.5% per surface
Transmission:	> 95%
Frequency shift:	110MHz
VSWR:	< 1.2:1
Active aperture:	2mm
Input polarisation:	Any
Diffraction efficiency:	> 85%
Rise-time:	155ns/mm
RF power:	< 2W (wavelength dependent)
VSWR:	< 1.2:1



光技術をサポートする  
**株式会社オプトサイエンス**  
<http://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング  
TEL: 03 (3356) 1064 FAX: 03 (3356) 3466 E-mail: info@optoscience.com  
大阪支店 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館  
TEL: 06 (6305) 2064 FAX: 06 (6305) 1030 E-mail: osk@optoscience.com  
名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル  
TEL: 052 (569) 6064 FAX: 052 (569) 8064 E-mail: ngo@optoscience.com

### Ordering Code

**Explanation: I-FS110-2C2B8-3-GH2** (Frequency shifter, 110MHz, 2.0mm active aperture, compressional mode, tellurium dioxide, 480 - 800nm, SMA female bulk head RF connector, GH2 housing).

I	-	F	S	1	1	0	-	2	C	2	B	8	-	3	-	G	H	2
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

