



MULTIMODE COMPONENTS

ITF Labs' Multimode Pump Combiners feature exceptional optical characteristics. These devices can be used to combine the power from several multimode laser diodes, delivering the combined power for applications in industrial, military, medical and telecommunications markets.

ITF Labs' "all glass" Multimode Combiners offer efficient power transfer for high power applications like direct diode materials processing and pump cascading with a maximum conservation of brightness. The Multimode Combiners can be designed to meet a wide range of power handling configurations, number of input fibers and adaptation to different fiber types.

HIGH POWER Pump Combiners For Direct Pumping Applications



For more information on this or other products and their availability, please contact our customer service at **514.748.4848** (Int'l) / **1.888.922.1044** (Canada & USA only) or via e-mail at info@itflabs.com

KEY FEATURES

- High Power Transfer Efficiency
- Wavelength Insensitive
- Custom Configurations Available
- RoHS Compliant



光技術をサポートする
株式会社オプトサイエンス
<http://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング
TEL: 03 (3356) 1064 FAX: 03 (3356) 3466 E-mail: info@optoscience.com
大阪支店 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館
TEL: 06 (6305) 2064 FAX: 06 (6305) 1030 E-mail: osk@optoscience.com
名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル
TEL: 052 (569) 6064 FAX: 052 (569) 8064 E-mail: ngo@optoscience.com

MULTIMODE COMPONENTS

HIGH POWER Pump Combiners For Direct Pumping Applications

SPECIFICATIONS

STANDARD CONFIGURATIONS

Product Code	MMC070110E1	MMC07012091	MMC13012091	MMC19012091*	MMC19012011	MMC190130J1*
Optical Specifications						
Pump Operating Wavelength	800-1000 nm					
Number of Multimode Inputs	7		13		19	
Number of Signal Ports	0					
Number of Output Ports	1					
Pump Input Fiber Core/clad diameter NA	105/125 μm 0.15	105/125 μm 0.22			200/220 μm 0.22	
Output Fiber Core/clad diameter NA	220/242 μm 0.22	400/440 μm 0.22			600/660 μm 0.22	800/880 μm 0.22
Power per Multimode Input Total Power	100 W 700 W		50 W 650 W		25W 475W	
Multimode Power Transfer Insertion Loss	0.5 dB	0.3 dB		0.5 dB		0.3 dB
Optical Return Loss - Pumps	45 dB					
Mechanical Specifications						
Dimensions	60 x 12 x 6.5 mm					
Fiber Pigtail Length Input/Output (1)	A= 1000 mm B= 2000 mm C= 3000 mm					

* Specified for NA=0.15 launch.
(1) Pricing is dependant on fiber pigtail length.

ORDERING INFORMATION

For standard products, please use product codes specified above.
ITF Labs can also develop custom multimode power combiners to meet
a wide range of technical requirements.



ITF Labs
400 Montpellier Blvd
Montreal, Quebec H4N 2G7 CANADA
Tel: 514.748.4848
Fax: 514.744.2080
1.888.922.1044
www.itflabs.com info@itflabs.com