



BrightLase[®] Collimated Module

Applications

- Printing
- Industrial
- Direct diode medical
- Vapor pumping

Features

- 810 nm, 1064 nm
- Custom wavelengths available
- Conduction cooled package

Benefits

- Extreme spatial brightness



	ES-156	ES-121
Output power	25 W	30 W
Operating Current	<38 A	<58 A (50 A typical)
Operating voltage	<1.9 V	<2 V (1.4 V typical)
Wavelength	810 nm +/- 10 nm	1064 nm +/- 10nm
Spectral width (FWHM)	≤ 5 nm	≤ 8 nm
Max beam divergence (x), 95% power enclosure	<12 mrad	≤ 9 mrad
Max beam divergence (y), 95% power enclosure	<6 mrad	≤ 6 mrad
Max beam size (x)	<8 mm	<10 mm
Max beam size (y)	<6 mm	<6 mm
Polarized mode	TE 100:1	TE 100:1
Package type	Sealed	Sealed
Module size (L x W x H)	100mm x 41.5mm x 31.5mm	100mm x 41.5mm x 31.5mm
Operating/Test temperature	+25° C +/-0.5	+25° C +/-0.5°C
Internal thermister	NTC 10K Ω	NTC 10K Ω



光技術をサポートする
株式会社オプトサイエンス
<http://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング
 TEL:03(3356)1064 FAX:03(3356)3466 E-mail:info@optoscience.com
 大阪支店 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館
 TEL:06(6305)2064 FAX:06(6305)1030 E-mail:osk@optoscience.com
 名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル
 TEL:052(569)6064 FAX:052(569)8064 E-mail:ngo@optoscience.com

BRIGHTNESS and POWER
Breaking Performance Barriers through Semiconductor Laser Innovation

QPC Lasers, Inc.

15632 Roxford Street • Sylmar, CA 91342 • Phone: +1 (818) 986-0000 • Fax: +1 (818) 698-0428

www.QPCLasers.com • email: info@QPCLasers.com



