

**Cutting Edge Optronics, Inc.**

20 Point West Blvd.

St. Charles, MO 63301

**Phone:** 636-916-4900 • **Fax:** 636-916-4994**Email:** st-ceolaser-info@ngc.com • **Website:** www.as.northropgrumman.com/ceolaser**Item # REA4006-1C2H, CW Laser Modules - Nd:YAG****QUOTE****CW Laser Modules - Nd:YAG**

CEO's CW pumped REA laser module is the ideal building block for any DPSS Laser system. Design flexibility allows for a variety of rod lengths, diameters, and gain media (Nd:YAG and Nd:YLF) to be used in both resonator and amplifier designs. CW output powers range from 140W to 650W.

*All prices displayed are US Domestic (per unit / low quantity) prices; please contact us for higher volume price structure.*

**SPECIFICATIONS**

Power	140 W
Number of Diode Bars	30
Power Per Bar	20 W
Pump Power	600 W
Rod Type	Nd:YAG
Rod Diameter	4 mm
Rod Length	126 mm
Diode Construction	Golden Bullet (hard solder)
Operation	CW



光技術をサポートする

**株式会社オプトサイエンス**<http://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング  
 TEL: 03 (3356) 1064 FAX: 03 (3356) 3466 E-mail: info@optoscience.com  
 大阪支店 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館  
 TEL: 06 (6305) 2064 FAX: 06 (6305) 1030 E-mail: osk@optoscience.com  
 名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル  
 TEL: 052 (569) 6064 FAX: 052 (569) 8064 E-mail: ngo@optoscience.com