

EX1 testing and monitoring solution

SIMPLE, MULTIPURPOSE, CARRIER-GRADE AND OPEN PLATFORM



EXFO's EX1 is an industry first: a pocket-sized test solution that evolves with your network, from validating bandwidth speed up to full line rate Gigabit Ethernet, to monitoring residential and business customers' quality of experience.

SPEC SHEET

KEY FEATURES AND BENEFITS

Gigabit Tester

Carrier-grade quality hardware including onboard FPGA power—delivering repeatable and reliable metrics each time

Powered by the industry-leading Speedtest® by Ookla® algorithm

Electrical and optical* interface ready

Rechargeable Li-ion battery operated

Provides latency, download and upload throughput performance metrics

Ookla server information and client WAN IP information reporting

Android™ and iOS®-supported smart devices

Controlled entirely through Android or iOS smart devices offering an “untethered experience” for setup, testing, report generation as well as cloud-enabled firmware upgrades

Test free and clear of challenging or harsh testing environments with Bluetooth® low energy technology for a connection range up to 100 ft (30 m)

Adjustable pass/fail thresholds based on subscribers' purchased plans

Efficient job closeout with automated report generation—reports generated in PDF or CSV formats are sent by email directly to the subscriber or shared through the EXFO Connect cloud service

Active Verifier*

Scalable platform capable of hosting EXFO's Active Verifier VNF for service and application performance assurance

As a Verifier, complete visibility of layer 3 to layer 7 performance through a suite of 140 different performance tests

As a Verifier, centralized management and control via EXFO Worx, with support for template-driven testing and automation from extensive API support



光技術をサポートする
株式会社オプトサイエンス

<http://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング TEL:03-3356-1064
大阪営業所 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館 TEL:06-6305-2064
名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル TEL:052-569-6064

E-mail : info@optoscience.com

EXFO

The EX1 is a one-of-a-kind Ethernet tester, paired with an Android or iOS smart device, to qualify broadband connections delivered to both residential and business Ethernet customers—enabling service providers to validate delivery of full line rate Gigabit Ethernet speeds to their subscribers. The EX1 advantage is two-fold: it includes FPGA-powered hardware, as well as the industry-leading Speedtest by Ookla algorithm, providing latency and download/upload throughput measurements. This allows service providers to obtain repeatable and reliable metrics, every time.

The EX1 does not require a screen. Instead, its ultra-intuitive application runs directly on a field technician's smart device to visualize all tasks performed including connection, setup, results-gathering, report generation and cloud-enabled firmware upgrades.

A flexible platform that evolves with your network, the EX1 can also host EXFO's Active Verifier VNF^a to deliver a complete level 3 to level 7 service assurance solution—integrated into the same compact EX1 platform. When activated, the Verifier capability opens up a world of possibilities: the Verifier VNF^a running in the EX1 platform can leverage a full suite of more than 140 performance tests to commission, assure and troubleshoot service performance and delivery across multiple layers. The test catalog includes support for service activation suites like Y.1564 SAM, IP connectivity tests, VoIP qualification, internet experience and infrastructure assurance that helps users assure the configuration and delivery of highly differentiated services.

The EX1 can be left on-site for temporary troubleshooting or permanently deployed as a fixed performance endpoint that continuously reports on network and service performance. It can also leverage the full capabilities of the EXFO Worx management system to facilitate test creation, aggregate performance results and integrate into any existing OSS/BSS as a data source.

SPECIFICATIONS

GENERAL SPECIFICATIONS

Size (H x W x D)	125 mm x 75 mm x 45 mm (5 in x 3 in x 1 3/4 in)
Weight	0.45 kg (1 lb)
Temperature	
Operating	0 °C to 40 °C (32 °F to 104 °F)
Storage	
With battery (short term < 1 month)	-10 °C to 40 °C (14 °F to 104 °F)
Relative humidity range	≤ 93 %, non-condensing

INTERFACES

Electrical RJ45 test port	10/100/1000 Mbit/s
Optical SFP test port ^a	Optical 1GE SFP
USB port	USB 3.0 Type-C port
Bluetooth and WiFi	Bluetooth v4.2 and WiFi 802.11 ac/a/b/g/n
Processor	ARM Dual Cortex-A53 ARMv8 1.0 GHz
Memory	1 GB
Storage	8 GB

BATTERY/POWER SUPPLY

Type	Rechargeable Li-ion smart battery
Battery autonomy	One full day of customer visits (i.e. average of 10 residential broadband customer visits)
Charging time	3.5 h using supplied wall charger
AC/DC adapter/charger	Input: 100 – 240 Vac; 50/60 Hz; 1.0 A max, output: 5 V; 2.4 A

SMART DEVICE REQUIREMENTS

Smart device supported	Android OS and iOS based devices
OS version	Android 6.0 Marshmallow and higher, iOS 10 and higher
Bluetooth support	Bluetooth low energy technology (version 4.0 and higher) ^b

Notes

a. Future capability.

b. Many Android phones and tablets support Bluetooth low energy technology, especially if the device was purchased recently. To verify if supported, please check if Bluetooth low energy technology (version 4) compatibility is listed in the technical specifications of smart devices in question.

1GE TESTING CAPABILITIES

Speedtest by Ookla	<ul style="list-style-type: none"> Latency Download speed Upload speed Server information Client WAN IP Automatic/manual server selection Pass/fail verdict based on thresholds Configurable job information PDF/CSV automatically generated reports
--------------------	---

VERIFIER CAPABILITY ^a

Turn-up tests	<ul style="list-style-type: none"> Y.1564 SAM IPerf
Layer 3 - Layer 7 active tests	<ul style="list-style-type: none"> Ping/traceroute One-way IP performance Two-way active measurement protocol (TWAMP) TCP/UDP echo TCP/UDP bandwidth measurements SIP VoIP signaling and media performance IPTV assurance Web quality and infrastructure Full suite of more than 140 performance tests available

Note

a. Future capability.

EXFO Headquarters > Tel.: +1 418 683-0211 | Toll-free: +1 800 663-3936 (USA and Canada) | Fax: +1 418 683-2170 | info@EXFO.com | www.EXFO.com

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. **Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.**

For the most recent version of this spec sheet, please go to www.EXFO.com/specs.

In case of discrepancy, the web version takes precedence over any printed literature.

Android is a trademark of Google Inc.

Ookla and Speedtest are registered trademarks of Ookla

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.

iOS is a registered trademark of Cisco System, Inc. and/or its affiliates in the U.S. and certain other countries.