



Multimode Components



Key Features

High ORL

Low Beam Distortion

Large Beam Expansion

Applications

Fiber Laser Power Amplifiers

End Cap

ITF Labs' End Caps are designed for high power fiber laser and amplifier termination. They feature beam expansion to reduce output power density, and an optically flat termination angle, which reduces the back reflection to better than -35dB. They are designed for operation at high peak or average power, with minimal beam distortion. Versions are available with a variety of fibers, including PM designs, the principal axis of which is keyed and aligned to the output face angle.



For more Info

Please contact us at:

North America: **514.748.4848**
888.922.1044

Europe & Asia: **+33 (0) 1 69 80 57 50**
or via e-mail at info@itflabs.com



光技術をサポートする

株式会社オプトサイエンス

<http://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング
TEL: 03 (3356) 1064 FAX: 03 (3356) 3466 E-mail: info@optoscience.com
大阪支店 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館
TEL: 06 (6305) 2064 FAX: 06 (6305) 1030 E-mail: osk@optoscience.com
名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル
TEL: 052 (569) 6064 FAX: 052 (569) 8064 E-mail: ngo@optoscience.com



Multimode Components

End Cap

SPECIFICATIONS* STANDARD CONFIGURATIONS

Product Code	EC1003061	EC1005061	EC1004061	EC1007061	EC1009061	EC1008061
Optical Specifications						
Operating Wavelengths	1040-1080 nm					
Endcap Polished Angle (1)	6 +/-0.5°					
Output Beam Angle (2)	87 +/-1.5°					
Signal Input Fiber (3)						
Core/clad diameter	20/400 µm	PM 20/400 µm	25/250 µm	PM 25/250 µm	30/250 µm	PM 30/250 µm
NA	0.06/0.46	0.06/0.46	0.11/0.46	0.11/0.46	0.06/0.46	0.06/0.46
Maximum Power Handling - Signal	250 W					
Maximum Power Handling - Cladding (4)	25 W					
Output MFD (5)	270-390 µm		260-390 µm		200-300 µm	
Optical Return Loss - Signal	> 45 dB					
Mechanical Specifications						
Fiber Pigtail Length Input (6)	A= 1000 mm B= 2000 mm C= 3000 mm					

- (1) Angle from 0 to 10° available
- (2) From datum reference plane, see PSS
- (3) Custom fiber available on request
- (4) Device not designed to remove cladding light
- (5) For LP01 core injection. MFD evaluated at 13.5% clip level
- (6) Pricing is dependant on fiber pigtail length

Revised Jan 2012

*Specifications subject to change without notice.

ORDERING INFORMATION

For standard products, please use product codes specified above. ITF Labs can also develop custom products to meet a wide range of technical requirements.

ITF Labs
North America: 514.748.4848
888.922.1044
Europe and Asia: +33 (0)1 69 80 57 50
www.itflabs.com • info@itflabs.com

3SP Group
Strategic Partner