



PHASICS
The phase control company

SID4-UV-HR

UV WAVEFRONT SENSOR SENSITIVE DOWN TO 190 NM

Based on Phasics patented technology, the SID4 UV-HR wavefront analyzer offers both an unrivalled high resolution (355x280 measurements points) and a very great sensitivity (1 nm RMS) in the ultraviolet spectrum from 190 nm to 400 nm. Consequently, the SID4 UV-HR is perfectly adapted for optical components characterization (used in lithography, semiconductor...) and surface inspection (lens and wafers...).

APPLICATIONS: [Laser industry](#) | [Astronomy](#) | [Semiconductor](#) | [Aerospace](#)

SPECIFICATIONS

Wavelength range	190 - 400 nm
Aperture dimensions	13.8 x 10.88 mm ²
Phase spatial resolution	40 μm
Phase & Intensity sampling	355 x 280
Resolution (Phase)	1 nm RMS
Accuracy (Absolute)	10 nm RMS
Acquisition rate	30 fps
Real-time processing frequency	> 3 fps (full resolution)*
Interface	CameraLink
Dimensions	51 x 51.1 x 76 mm ³
Weight	~ 300g

* with SID4 software



光技術をサポートする
株式会社オプトサイエンス

<https://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング TEL:03-3356-1064
大阪営業所 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館 TEL:06-6305-2064
名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル TEL:052-569-6064

E-mail : info@optoscience.com