



Benefits:

- For cameras up to 40 x 40mm cross section
- Robust construction
- Compact size
- Small dead weight
- High IP protection class
- Flexible camera positioning
- High chemical resistance
- Vibration-proof mounting
- Camera mount included
- Excellent heat dissipation



Weight

Technical Details:

Max. Camera Size (w x h)	40 x 40mm 29 x 47mm
Max. Lens Diameter	55mm (in profile) 52mm (in front lid)
Inner Length	94 (Size XS) 136 (Size S) 189 (Size M) 219 (Size L)
Enclosure Dimensions (w x h x l, without cable gland)	66 x 66 x 108mm (Size XS) 66 x 66 x 150mm (Size S) 66 x 66 x 203mm (Size M) 66 x 66 x 233mm (Size L)
Window Aperture	45mm
Standard Window IR Mirror Saphire Germanium Acrylic, uncoated Acrylic, double sided ARC Window Seal	BK7, double sided ARC Order Number: 20.000.010 Order Number: 20.000.016 Order Number: 20.000.017 Order Number: 20.000.058 Order Number: 20.000.029
Williadw Scal	FKM

IP67 (Nema 6)

(without camera mount) Enclosure Material	Approx. 850g (Size S) Approx. 1070g (Size M) Approx. 1200g (Size L) Anodized Aluminum			
Enclosure Seals	NBR			
Cable Gland Aperture (max. connector size)	22mm (Rear Wall A) 13.5mm (Rear Wall B) 16.5mm (Rear Wall B) 26.5mm (Rear Wall C)			
Cable Diameter	4-6.5mm (Rear Wall B) Self drilling (Rear Wall C)			
Cable Gland Seal	TPE			

Approx. 660g (Size XS)



The mount guarantees excellent heat dissipation













Order Numbers:

Product ID	Camera Height	Camera Lenght	Enclosure Type	Rear Wall Type	Length
2	29: 0 30: 1 31: 2 32: 3 33: 4 34: 5 35: 6 36: 7 38: 8 40: 9	< 50mm: 3 < 74mm: 5 < 92mm: 7	1	A: 0 B: 1 C: 2 D: 3	XS: 070 S: 139 M: 192 L: 222


Accessories:

Product	Image	Order No.	Product	Image	Order No.	Product	Image	Order No.
Air Nozzle	100	50.100.025	Cooling Module		60.100.010	Mounting Kit 2	1	5.020.000
2" Wind Curtain	10	50.100.010	El. Heating Plate	No.	70.100.018	Mounting Kit 6	1	5.060.000
Tube for W. Curtain		50.100.017	Orca Adapter		15.030.001	Mounting Kit 7	2 0	5.070.000
Pneumatic Shutter		50.200.010	Sun Roof Size S, M		20.010.001 20.010.002	Mounting Kit 9	1	5.090.000
Deflection Mirror 90°	N. A.	20.020.004	Sun Roof Size L		20.010.003	Mounting Kit 10		5.100.000
30/60mm Extension	2	15.015.030 15.015.060	Corrugated Tube 28mm		20.000.006	Mounting Kit 15	V. VI	5.150.000
60mm Side Exit	160	15.015.061	Alignment Tool	6	90.000.014	Mounting Kit 16/16m	11	5.160.000 5.160.000m
Position Ring	O	20.020.003	Mounting Kit 1		5.010.000	Mounting Kit 17/17m	11	5.170.000 5.170.000m





Salamander Drawings























max. 16.5mm connector 4 - 6.5mm cable max. 13.5mm connector 4 - 6.5mm cable




Rear Wall C



max. 26.5mm connector several cables





Rear Wall D

