



# 10/125 & 10/130 Precision Matched Active LMA Double Clad Fibers

Nufern's matched series of Large Mode Area (LMA) double clad fibers are ideal for monolithic fiber lasers and amplifiers. Featuring a matching set of LMA fibers, this series of fibers ensure splice compatibility across the entire chain of 10/130 fiber components required to make monolithic fiber lasers. This matched fiber series is based on a 10 micron diameter core and 130 micron diameter clad size with a low NA (0.075) core and consists of Yb-doped fiber and passive beam delivery fibers all made to highest tolerances in the industry. All fibers utilize the latest glass composition and NuCOAT fluoroacrylate coating technology to ensure high slope efficiency, extended operating life and excellent beam quality demanded by today's industrial fiber laser applications. These precision matched LMA fiber sets are available in non-PM (LMA) and PM (PLMA) versions.

## Typical Applications

- Pulsed fiber lasers and amplifiers
- Material processing
- LIDAR
- Non-linear optics / frequency doubling

## Features & Benefits

- Matched fiber series – Ensures splice compatibility across the 10/130 matched series of fibers
- NuCOAT™ fluoroacrylate coating — Greater fiber durability in extreme environmental operating & storage conditions
- State of the art Yb-doped glass — Useful for generating high CW powers
- PANDA-style stress structure for increased birefringence — Superior optical performance and uniformity
- All fiber proof tested to > 100 kpsi — Critical for ensuring long term reliability when coiling

## Optical Specifications

	PLMA-YDF-10/125-M	LMA-YDF-10/130-M
Operating Wavelength	1060 – 1115 nm	1060 – 1115 nm
Core NA	0.075 ± 0.005	0.075 ± 0.005
First Cladding NA (5%)	≥ 0.460	≥ 0.46
Cladding Attenuation	≤ 15.0 dB/km @ 1095 nm	≤ 15.0 dB/km @ 1095 nm
Cladding Absorption	1.65 ± 0.15 dB/m at 915 nm 4.95 dB/m near 976 nm	1.35 ± 0.15 dB/m at 915 nm 4.10 dB/m near 975 nm
Birefringence	nominal $3 \times 10^{-4}$	N/A

## Geometrical & Mechanical Specifications

	PLMA-YDF-10/125-M	LMA-YDF-10/130-M
Cladding Diameter	125.0 ± 1.0 μm	N/A
Cladding Diameter (flat-to-flat)	N/A	130.0 ± 1.5 μm
Core Diameter	11.0 ± 1.0 μm	11.0 ± 1.0 μm
Coating Diameter	245.0 ± 10.0 μm	245.0 ± 10.0 μm
Coating Concentricity	< 5.0 μm	< 5.0 μm
Core/Clad Offset	≤ 0.70 μm	≤ 0.70 μm
Proof test Level	≥ 100 kpsi (0.7 GN/m <sup>2</sup> )	≥ 100 kpsi (0.7 GN/m <sup>2</sup> )

Coating Requirements: Low index polymer coating. The precision matched passive fibers are also available- see PLMA-GDF-10/125-M and LMA-GDF-10/130-M



7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • E-mail info@nufern.com • www.nufern.com • Nufern products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.



# 10/125 & 10/130 Precision Matched Passive LMA Double Clad Fibers

Nufern's large mode area (LMA) and Polarization Maintaining LMA (PLMA) passive double clad fibers are ideally suited for applications spanning military, industrial and medical including linearly polarized fiber lasers and amplifiers. These fibers feature a 10 micron diameter core and 125 (PLMA) or 130 (LMA) micron diameter clad size with a low NA (0.075) core. They are precision matched to their active Yb-doped 10/130 LMA and PLMA matched counterparts to ensure excellent splice compatibility and low loss. As with all Nufern standard Large Mode Area (LMA) fibers, these fibers are proof-tested to 100 kpsi, an industry requirement for long term reliability. They utilize the latest fiber design and NuCOAT™ coating technology to ensure excellent preservation of beam quality and extended operating life demanded by today's industrial fiber laser applications. These precision matched fibers are available in both non-PM and PANDA-style PM fibers.

## Typical Applications

- Pulsed fiber lasers and amplifiers
- Material processing
- LIDAR
- Non-linear optics / frequency doubling

## Features & Benefits

- NuCOAT™ fluoroacrylate coating — Greater fiber durability in extreme environmental operating & storage conditions
- LMA core design — Useful for transmitting high CW powers
- "Few" moded core design — Easy to maintain single mode LP01 beam through fiber & components
- PANDA-style stress structure for increased birefringence — Superior optical performance and uniformity
- All fiber proof tested to > 100 kpsi — Critical for ensuring long term reliability when coiling

## Optical Specifications

	PLMA-GDF-10/125-M	LMA-GDF-10/130-M
Operating Wavelength	1060 – 1600 nm	1060 – 1600 nm
Core NA	0.075 ± 0.005	0.075 ± 0.005
First Cladding NA (5%)	≥ 0.460	≥ 0.46
Core Attenuation	≤ 40.00 dB/km @ 1300 nm ≤ 20.00 dB/km @ 1200 nm	≤ 40.0 dB/km @ 1300 nm ≤ 20.0 dB/km @ 1200 nm
Cladding Attenuation	≤ 15.0 dB/km @ 1095 nm	≤ 15.0 dB/km @ 1095 nm
Birefringence	nominal $3 \times 10^{-4}$	N/A

## Geometrical & Mechanical Specifications

	PLMA-GDF-10/125-M	LMA-GDF-10/130-M
Cladding Diameter	125.0 ± 1.0 μm	130.0 ± 1.0 μm
Core Diameter	11.0 ± 1.0 μm	11.0 ± 1.0 μm
Coating Diameter	245.0 ± 10.0 μm	245.0 ± 10.0 μm
Coating Concentricity	< 5.0 μm	< 5.0 μm
Core/Clad Offset	≤ 0.70 μm	≤ 0.70 μm
Clad Non-Circularity	N/A	≤ 0.5 %
Proof-test Level	≥ 100 kpsi (0.7 GN/m <sup>2</sup> )	≥ 100 kpsi (0.7 GN/m <sup>2</sup> )

These precision matched fibers are included in our precision matched sets - see PLMA-YDF-10/125-M and LMA YDF-10/130-M



7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • E-mail info@nufern.com • www.nufern.com • Nufern products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.