

# 600 Micron Core Power Delivery Fiber



Coherent | Nufern's specialty multimode step-index fibers are designed for compatibility with the majority of fiber-coupled, bar and stack diode-laser packages and support the diode laser power delivery market. This fiber features a 600 micron core diameter with a 0.22 NA and a 660 micron clad diameter with Coherent | Nufern's proprietary NuCoat-FA, a low refractive index fluoroacrylate coating, for added power confinement. Other fiber diameters are available upon request.

## Typical Applications

- Fiber coupled diode lasers
- Couplers and pump combiners

## Features & Benefits

- 0.22 NA — Compatible with the majority of fiber-coupled, diode-laser packages
- Exceptional geometric uniformity and core/clad concentricity — Ease of coupling to pump diodes
- Pure silica core — High resistance to optical damage
- Clean room fiber draw — Eliminates coating "hot spots"
- All fiber proof tested to > 100 kpsi — Critical for ensuring long term reliability when coiling

## Optical Specifications

Operating Wavelength  
Core NA  
First Cladding NA (5%)  
OH Level

## MM-S600/660-22FA 1362303

700 – 2200 nm  
0.220 ± 0.020  
≥ 0.46  
Low

## Geometrical & Mechanical Specifications

Cladding Diameter  
Core Diameter  
Coating Diameter  
Core/Clad Offset  
Coating Material  
Short Term Bend Radius  
Long Term Bend Radius  
Proof test Level

660.0 ± 12.0 μm  
600.0 ± 12.0 μm  
875.0 ± 30.0 μm  
≤ 7.00 μm  
Low Index Acrylate  
≥ 34 mm  
≥ 100 mm  
≥ 100 kpsi (0.7 GN/m<sup>2</sup>)



Custom developed fiber (FOD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.



NU320-02/08/2018



光技術をサポートする  
株式会社オプトサイエンス

<https://www.optoscience.com>

東京本社 〒160-0014 東京都新宿区内藤町1番地 内藤町ビルディング TEL:03-3356-1064  
大阪営業所 〒532-0011 大阪市淀川区西中島7-7-2 新大阪ビル西館 TEL:06-6305-2064  
名古屋営業所 〒450-0002 名古屋市中村区名駅2-37-21 東海ソフトビル TEL:052-569-6064

E-mail : [info@optoscience.com](mailto:info@optoscience.com)