

PART NUMBER: ASM232P100  
GOLDEN BULLET SUBMODULE



### > FEATURES AND BENEFITS

- Proprietary Hard Solder Technology
- Long Pulse and/or High Duty Cycle
- Expansion Matched Materials
- Available Wavelengths (790-980nm)

### > OPTICAL CHARACTERISTICS

Parameter	Conditions	Min	Typ	Units
QCW Power Output	98A at 25°C Heat Sink	100	—	W
Operating Current	100W at 25°C Heat Sink	—	98	A
Threshold Current	25°C Heat Sink	—	15	A
Center Wavelength	100W at 25°C Heat Sink	—	808	nm
Wavelength Tolerance	100W at 25°C Heat Sink	—	+/-3	nm
Spectral Width	100W at 25°C Heat Sink	—	2.0	nm
Wavelength Shift	—	—	0.25	nm/°C
Beam Divergence FWHM	—	—	40x10	°x°

### > ELECTRICAL CHARACTERISTICS

Parameter	Conditions	Min	Typ	Units
Series Resistance	25°C Heat Sink	—	0.002	ohms
Operating Voltage	25°C Heat Sink, 100W	—	1.8	V

### > ABSOLUTE MAXIMUM RATINGS

Parameter	Conditions
Reverse Current	0A
Reverse Voltage	0V
Operating Temperature Range	-40°C to 70°C
Storage Temperature Range	-40°C to 85°C





### > NOTES

- (1) These specifications apply for operation at 808nm. Other wavelengths available upon request.  
 (2) A dry nitrogen environment should be provided by the user when storing and operating at temperatures below ambient dew point.




100W QCW

OPTICAL CHARACTERISTICS (TYPICAL)



MECHANICAL CHARACTERISTICS



Copyright © 2008 Northrop Grumman Cutting Edge Optronics All Rights Reserved. Northrop Grumman Cutting Edge Optronics reserves the right to change product design and specifications at any time without notice. No license is granted by implication or otherwise under any patents or patent rights of Northrop Grumman Cutting Edge Optronics or others. No responsibility is assumed for the use of these products, nor for any infringement on the rights of others resulting from the use of these products. Information contained herein is believed to be reliable and accurate. Laser diode product components are intended for use in a user-devised end system. However, these products are capable of emitting Class IV radiation. Extreme care must be exercised during their operation. Only persons familiar with the appropriate safety precautions should operate a laser product. Directly viewing the laser beam or exposure to specular reflections must be avoided. Serious injury may result if any part of the body is exposed to the beam. The eye is extremely sensitive to the infrared radiation and therefore, proper eyewear must be worn at all times. Use of optical instruments with these products may increase eye hazard. Always wear proper eye protection when operating. This Product is covered by one or more of the following Patents: 5,898,211 | 5,985,684 | 5,913,108 | 6,310,900 | Other US and Foreign Patents Pending. Notes (1) These specifications apply for operation at 808nm. Other wavelengths available upon request. (2) A dry nitrogen environment should be provided by the user when storing and operating at temperatures below ambient dew point.

**⚠ DANGER ⚠**

INVISIBLE LASER RADIATION

AVOID EYE OR SKIN EXPOSURE TO DIRECT OR SCATTERED RADIATION

\* Diode laser  
SW & up, 790-1560nm  
CLASS IV

---

**⚠ WARNING ⚠**

ELECTROSTATIC DISCHARGE SENSITIVE DEVICE  
REQUIRING SPECIAL HANDLING

Rev. A 02/08 ISO 9001:2000 Registered